



WAND- UND DECKENFARBE

White interior wall color
Matt
Solvent-free, emission-minimised
Good coverage
Diffusion-capable
Easy to apply
Wet abrasion class 4 (DIN EN 13300)



DESCRIPTION: White, matt emulsion paint designed for interior use only.	drying time: (at 20°C, 65% rel. humidity) touchdry: abt. 2 - 3 hrs. dry to recoat: abt. 8 hrs.
light resistance: good weather resistance: not suitable for outdoor use compatibility: miscible with all full and tint colors in any ratio	Lower temperatures and higher humidity extends the drying time! INGREDIENTS: Acrylate-copolymer-binder, titanium dioxide, carbonate and silicate fillers, white pigments, water, additives, preservative: 1,2-Benzisothiazol-3 (2H)-one, can cause allergic reactions. Advice for isothiazolinone allergy sufferers under Phone no.: +49 4124-606-188.
USAGE: Dispersion paint for slightly stressed wall and ceiling surfaces in the indoor / living area, cellar rooms and garages. Excellent for wall and ceiling surfaces indoors. As an economical renovation coat for normal requirements.	VOC-content: EU-Limit for Wand- und Deckenfarbe(Kat.A/a) 30 g/l (2010). Wand- und Deckenfarbe contains maximum 5 g/l VOC.
GUIDELINES FOR APPLICATION: A corresponding professional pretreatment of the substrate is crucial for a good permanent coating. The substrate must be firm, load-bearing, clean, dry and free from efflorescence, discolouration, fungal attack, sintering, powdered granules and separating substances. Existing old coatings must be tested for suitability, adhesion and load bearing capacity. Very smooth surfaces roughen. Strongly absorbing and sanding surfaces with deep base LF. Remove loose paints. Application can be done by painting, rolling or spraying.	WGK: 1 GISBAU-Code: M-DF 02
COATING SYSTEMS: 1. on plaster and concrete, inside a) pretreatment: 1x priming with Tiefengrund b) base coat: Wand- und Deckenfarbe thinned with 10% clean water c) finish: 1 - 2 coats Wand- und Deckenfarbe 2. recoating of old paint layers or renovation painting a) pretreatment: cleaning b) depending on the surface 1 – 2 coats with Wand- und Deckenfarbe	HAZARDS / SAFETY PRECAUTIONS Even when working with low-emission paints the usual protective measures must be observed - Keep away from children - If medical advice is needed, show product drum or label.- Spraying - do not inhale spray mist - when spraying use combination filter A2 / P2, when grinding use dust filter P2 - during application and drying for good ventilation - in contact with eyes or skin, immediately rinse thoroughly with water - do not allow to enter into surface water or drains - eating, drinking and smoking during use of color should be avoided – wear suitable protective clothing, gloves and safety glasses when working – store dry and cool. Protect from frost. Follow all relevant local or national health, safety and environmental regulations of legislator and trade association. Prior to use, read and follow strictly all notices on the material safety data sheet.
consumption: abt. 5 - 6 m ² /ltr., for one coating depending on the absorbency of the substrate thinner for rolling, brushing, spraying: water tools: paint brush, paint roller, airless spraying cleaning of tools: immediatly after use with water and soap	colour shades white packaging sizes: 10 L
	These technical data are given to you for information purpose only. They are based on our own research and experiences. No responsibility can be assumed due to different conditions during application. As these depend on factors beyond our control. In case of doubt, please consult our technical / service department. Data are subject to change without prior notice and become void five years from the date issue.