tesa® 4024



Product Information

Universal carton sealing tape

Manual and automatic sealing of light and medium-range weight cartons.

Features

tesa® 4024 PV 2 is based on a PP backing coated with a special high tack water based acrylic adhesive. The excellent tack of the adhesive secures a good sealing immediately after application.

Main Application

Manual and automatic sealing of light and medium-range weight cartons.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

| • | Backing material | PP film | • | Elongation at break | 140 % |
|---|------------------|---------|---|---------------------|---------|
| • | Total thickness | 52 μm | • | Tensile strength | 45 N/cm |
| • | Type of adhesive | acrylic | | | |

Adhesion to

• steel 3.0 N/cm

Properties

| • | Automatic application | Yes | • | Printability | ••• |
|---|-----------------------|-----|---|---------------------|-----|
| • | Manual application | Yes | • | Low noise unwinding | Yes |

Evaluation across relevant tesa® assortment: •••• very good ••• good •• medium • low

Additional Information

The PV3-version of the product is printable.

tesa® 4024 Product Information



Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

