



				>80 CRI	W 3000 K	N 4000 K	IP65 EN 60529	230 V 2014/35/UE	50/60 Hz	IK07 EN 60068	850° EN 60695
	RG 0 EN 62471				CAE ON/OFF	02 BLACK	05 SILVER	5Y WARRANTY 5% FAILURE RATE	60.000 h LED LIFETIME L90B10		

IT

Corpo in nylon autoestinguente ed infrangibile, colore nero.

Riflettore in alluminio verniciato.

Diffusore in polycarbonato autoestinguente V2, con prismatura interna, stabilizzato ai raggi UV e trattato contro l'ingiallimento.

Alimentatore elettronico ON/OFF.

Sorgente luminosa LED.

Emissione diretta.

Idoneo per l'installazione all'esterno.

EN

Unbreakable and self-extinguishing nylon body, colour black.

Reflector in painted aluminium.


Diffuser in transparent self-extinguishing V2 polycarbonate with internal cafets, ultra-violet stabilized and treated against yellowing.

ON/OFF electronic driver.

LED light source.

Direct light emission.

Suitable for outdoor installation.



DEDRO



Code	Lm Out	Watt Out	Lm/Watt Out
KDDR20LDW/N02	2000	20	100
KDDR20LDW/N05	2000	20	100
KDDR10LDW/N02	1000	10	100
KDDR10LDW/N05	1000	10	100

W/N= **W** (3000 K) **N** (4000 K)